



## POLY R.I.T.E

POLY R.I.T.E is an expanded polystyrene cored high density laminated insulation board. Clear or metallic foil polypropylene film can be used to laminate it. The strength of POLY R.I.T.E provides a high standard of protection while also improving the insulation of your residential or commercial project. This Laminated sheathing board lays flat against the wall, is exceptionally durable, lightweight, and is easy to install. POLY R.I.T.E laminated insulation provides excellent R-Value and helps to conserve energy. It also resists moisture, decreasing the risk of mold and mildew. POLY R.I.T.E is available in densities from 25psi to 60 psi. It comes in standard 4' x 8' and 2' x 8' sheets with thicknesses ranging from 3/8" to 2".

POLY R.I.T.E BOARD	Compressive Strength*	R- VALUE 75° F	R- VALUE 40° F
TYPE IX	25 PSI	4.4	4.8
TYPE XIV	40 PSI	4.5	4.8
TYPE XV	60 PSI	4.6	5.0

### USES

POLY R.I.T.E is successfully used in numerous applications in both commercial and residential construction. For example:

- ◆Interior/exterior wall insulation
- ◆Single ply roof insulation
- ◆Below grade Insulation
- ◆Retaining walls
- ◆Foundation perimeter
- ◆Basement Insulation
- ◆Drainage boards
- ◆Waterproofing protectionboard
- ◆Freezer and cold storage



96 4th Avenue Haskell, NJ 07420

(973) 835-7161

[www.polymoldingllc.com](http://www.polymoldingllc.com)